


Wiring Configuration


La Configuration des alimentations. Die Konfiguration der Stromanschlüsse. Verdrahtungs Konfiguration



Wired Direct (Standard Direct, Télégraphique Direct, Direct hat verdrahtet)

A 4Ω speaker will represent a 4Ω load.


(Un 4Ω speaker représentera une charge 4Ω. Un 4Ω haut-parleur représentera un 4Ω charge.) (Ein 4Ω Speaker bedeutet eine 4Ω Last.)



Two Speakers wired in parallel (Deux Oncteurs alimentés en le parallèle. Deux Haut-parleurs ont télégraphié direct l'un à l'autre. Zwei Speaker haben parallel verdrahtet)

A 4Ω speaker will represent a 2Ω load.


(Un 4Ω speaker représentera une charge 2Ω. Un 4Ω haut-parleur représentera un 2Ω charge.) (Ein 4Ω Speaker bedeutet eine 2Ω Last.)



Four Speakers wired in parallel (Quatre Oncteurs alimentés en le parallèle. Quatre Haut-parleurs ont télégraphié direct l'un à l'autre. Vier Speaker haben parallel verdrahtet)

A 4Ω speaker will represent a 1Ω load.

(Un 4Ω speaker représentera une charge 1Ω. Un 4Ω haut-parleur représentera un 1Ω charge.) (Ein 4Ω Speaker bedeutet eine 1Ω Last.)



Three Speakers wired in parallel (Trois Oncteurs alimentés en le parallèle. Trois Haut-parleurs ont télégraphié direct l'un à l'autre. Drei Speaker haben parallel verdrahtet)

A 4Ω speaker will represent a 1.33Ω load.

(Un 4Ω speaker représentera une charge 1.33Ω. Un 4Ω haut-parleur représentera un 1.33Ω charge.) (Ein 4Ω Speaker bedeutet eine 1.33Ω Last.)

Maximize your subwoofers performance  
**STREET WIRES**  
www.streetwires.com


MTX products purchased in the USA from an authorized MTX dealer are guaranteed against defects in material and workmanship for a period of 1 year, the warranty period begins the day the product is purchased by the end user. This warranty is limited to the original retail price of product. Product found to be defective during that period will be repaired or replaced by MTX at no charge. This warranty is void if it is determined that unauthorized parties have attempted repair or alterations of any nature. Warranty does not extend to accidents or abuse. Before presenting a defect to present in the product, the customer shall submit the equipment and wiring in functioning properly. MTX disclaims any liability for other financial damages resulting from product deficiencies. Any expense in the removal or installation of products are not covered by this warranty. MTX's retail labels will not extend the purchase price of the product. It is dealer's prerogative your authorized MTX dealer may be able to offer a better repair.

Proof of purchase is required when requesting service, so please retain your sales receipt, and take a moment to register your product on line at MTX.com. Also, a Return Authorization number (RA) is required before shipping product back to MTX, call 800-606-0888 or 800-606-0888 for speaker RA.

Parameters



Los parámetros. Paramètres. Parameter

- F<sub>c</sub> 38.7 Hz
- Q<sub>ms</sub> 5.32
- C<sub>ms</sub> 0.148 mm/H
- R<sub>ms</sub> 114.59 g
- R<sub>ms</sub> 5.225 kg/s
- V<sub>max</sub> 1.060 ft<sup>3</sup> (29.97 liters)
- X<sub>max</sub> 0.370 in (9.40 mm)
- S<sub>d</sub> 8.661 in (220.00 mm)
- S<sub>d</sub> 58.32 in<sup>2</sup> (380.13 cm<sup>2</sup>)
- V<sub>d</sub> 21.80 in<sup>3</sup> (0.36 liters)
- Q<sub>es</sub> 0.64
- R<sub>e</sub> 3.50 Ω
- B<sub>1</sub> 12.30 Tm
- F<sub>ms</sub> 200 Watts
- Q<sub>ts</sub> 0.470
- η<sub>0</sub> 0.262 %
- SPL<sub>0</sub> 86.4 dB
- SPL<sub>2</sub> 23V1m: 90.0 dB



Specifications

Les spécifications. Spöifications. Spezifikationen



Recommended Power Rating of 100 - 200 Watts RMS

La Potencia nominal recomendada. Le Puissance recommandée. Empfohlene Kraft-Einstufung



TRINNER - JACKHAMMER - AXE - SUBHAMMER - TRINNERFROM  
AMPLIFIERS - SUBWOOFERS - SPEAKERS - ENCLOSURES - MARINE **MTX**

2149028

Sealed Enclosure

El Cerrco sellado. Cofre sellado. Abgeschlossene Encloshung


For the best possible sound quality where space is a premium, MTX recommends using a sealed enclosure. For excellent sound quality with increased output compared to sealed enclosures (3dB or more), MTX recommends using a vented enclosure. All recommended enclosures have been designed and thoroughly tested by MTX.




Net Internal Volume: 0.75 ft<sup>3</sup>

Parts List


La Lista de partes. Liste de parties. Ersatzteilliste




[A] - 3/4" (19mm) MDF



[B] - 3/4" (19mm) MDF



[C] - 3/4" (19mm) MDF





[D] - 3/4" (19mm) MDF

Vented Enclosure

Descarga Cerrco. Cofre con abertura vent. Vented Encloshung


For the best possible sound quality where space is a premium, MTX recommends using a sealed enclosure. For excellent sound quality with increased output compared to sealed enclosures (3dB or more), MTX recommends using a vented enclosure. All recommended enclosures have been designed and thoroughly tested by MTX.



Net Internal Volume: 1.45 ft<sup>3</sup>

Parts List

La Lista de partes. Liste de parties. Ersatzteilliste




[A] - 3/4" (19mm) MDF




[B] - 3/4" (19mm) MDF




[C] - 3/4" (19mm) MDF



[D] - 3/4" (19mm) MDF



[E] - 3/4" (19mm) MDF



[F] - 3/4" (19mm) MDF