mtx audio

THUNDER 55

TS5510-22

Wiring Configuration

La Configuración del alambrado, La Configuración del alambrado, Verdrahtende Konfiguration

Wired Direct *(Alambró Directo, Télégraphié Direct, Direkt hat verdrahtet):*

A 4Ω speaker will represent a 4Ω load.

(Un orador 4Ω representará una carga 4Ω, Un 4Ω haut-parleur représentera un 4Ω chargerl, Ein 4Ω Sprecher beladen eine 4Ω wird vertreten)



Two Speakers wired in parallel *(Dos Oradores alambraron en la paralela, Deux Haut-parleurs ont télégraphié dans l'analogie, Zwei Sprecher haben parallel verdrahtet):*

A 4Ω speaker will represent a 2Ω load.

(Un orador 4Ω representará una carga 2Ω, Un 4Ω haut-parleur représentera un 2Ω chargerl, Ein 4Ω Sprecher beladen eine 2Ω wird vertreten)



Four Speakers wired in parallel *(Cuatro Oradores alambraron en la paralela, Quatre Haut-parleurs ont télégraphié dans l'analogie, Vier Sprecher haben parallel verdrahtet):*

A 4Ω speaker will represent a 1Ω load.

(Un orador 4Ω representará una carga 1Ω, Un 4Ω haut-parleur représentera un 1Ω chargerl, Ein 4Ω Sprecher beladen eine 1Ω wird vertreten)

Three Speakers wired in parallel *(Tres Oradores alambraron en la paralela, Trois Haut-parleurs ont télégraphié dans l'analogie, Drei Sprecher haben parallel verdrahtet):*

A 4Ω speaker will represent a 1.3Ω load.

(Un orador 4Ω representará una carga 1.3Ω, Un 4Ω haut-parleur représentera un 1.3Ω chargerl, Ein 4Ω Sprecher beladen eine 1.3Ω wird vertreten)

Maximize your subwoofer's performance
STREETWIRES
structwire.com

MTX products purchased in the USA from an authorized MTX dealer are guaranteed against defects in material and workmanship for a period of 1 year, the warranty period begins the day the product is purchased by the end user. This warranty is limited to the original retail purchaser of product. Product found to be defective during that period will be repaired or replaced by MTX at no charge. This warranty is void if it is determined that unauthorized parties have attempted repairs or alterations of any nature. Warranty does not extend to cosmetics or finish. Before presuming a defect is present in the product, be certain that all related equipment and wiring is functioning properly. MTX disclaims any liability for other incurred damages resulting from product defects. Any expense in the removal or reinstallation or products are not covered by this warranty. MTX's total liability will not exceed the purchase price of the product. If a defect is present, your authorized MTX dealer may be able to effect repairs.

Proof of purchase is required when requesting service, so please retain your sales receipt, and take a moment to register your product on line at MTX.com. Also, a Return Authorization number (RA) is required before shipping product back to MTX, call 800-556-2888 or 858-328-5560 for speaker RA's.

mtx audio

THUNDER 55

TS5510-22

Parameters

Los parámetros, Paramètres, Parameter

F_s: **37 Hz**
Q_{ms}: **8.81**
C_{ms}: **0.088** mm/N
M_{ms}: **205.9** g
R_{ms}: **5.49** kg/s
V_{as}: **0.992** ft³ (**28.18** liters)
X_{max}: **0.600** in (**15.20** mm)
D: **8.52** in (**278.69** mm)
S_d: **73.90** in² (**476.7** cm²)
V_d: **44.34** in³ (**0.73** liters)
Q_{es}: **0.810**
R_e: **.85** Ω
B_l: **7.10** Tm
P_{rms}: **450** Watts
Q_{ts}: **0.742**
η_0: **0.173** %
SPL: **84.5** dB
$SPL_{2.83V/1m}$: **94.24** dB



Specifications

Las especificaciones , Spécifications, Spezifikationen





Recommended Power Rating of 225 - 450 Watts RMS

La Potencia nominal recomendada, Le Pouvoir recommandé Evaluant, Empfohlene Kraft Einzuschätze

THUNDER™ - JACKHAMMER™ - AXE - SLEDGEHAMMER™ - THUNDERFORM™
AMPLIFIERS - SUBWOOFERS - SPEAKERS - ENCLOSURES - MARINE
MTX AUDIO

21A0072

mtx audio

THUNDER 55

TS5510-22

Sealed Enclosure

El Cerco sellado, Clôture scellée, Abgedichtete Einschließung

For the best possible sound quality where space is a premium, MTX recommends using a sealed enclosure. For excellent sound quality with increased output compared to sealed enclosures (3dB or more), MTX recommends using a vented enclosure. All recommended enclosures have been designed and thoroughly tested by MTX.





Net Internal Volume: 1.00 ft³

Parts List

La Lista de partes, Liste de parties, Ersatzteilliste



[A] – 3/4" (19mm) MDF



[B] - 3/4" (19mm) MDF



[C] - 3/4" (19mm) MDF



[D] - 3/4" (19mm) MDF

(Para la mejor calidad sano posible donde espacia es una prima, MTX recomienda utilizando un cerco sellado. Para la calidad sano excelente con la producción aumentada comparó con cercos sellados (3dB o más), MTX recomienda utilizando un descargar cerco. Todos cercos recomendados se han diseñado y han sido probados completamente por MTX.)
(Pour la qualité solide le mieux possible où l'espace est une prime, MTX recommande utilisant une clôture scellée. Pour la qualité solide excellente avec le production augmenté en comparaison des clôtures scellées (3 dB ou plus), MTX recommande utilisant une clôture donnée vent. Toutes clôtures recommandées ont été conçues et ont été essayées à fond par MTX.)
(Für die bestmögliche gesunde Qualität, wo sperrt eine Prämie ist, empfiehlt MTX daß das Benutzen von einer abgedichteten Einschließung. Für ausgezeichnete gesunde Qualität gibt mit vermehrt

mtx audio

THUNDER 55

TS5510-22

Vented Enclosure

Descargar Cerco, Clôture donnere vent, Vented Einschließung

For the best possible sound quality where space is a premium, MTX recommends using a sealed enclosure. For excellent sound quality with increased output compared to sealed enclosures (3dB or more), MTX recommends using a vented enclosure. All recommended enclosures have been designed and thoroughly tested by MTX.





Net Internal Volume: 1.45 ft³

Parts List

La Lista de partes, Liste de parties, Ersatzteilliste



[A] – 3/4" (19mm) MDF



[B] - 3/4" (19mm) MDF



[C] - 3/4" (19mm) MDF



[D] - 3/4" (19mm) MDF



[E] - 3/4" (19mm) MDF



[F] - 3/4" (19mm) MDF

(Para la mejor calidad sano posible donde espacia es una prima, MTX recomienda utilizando un cerco sellado. Para la calidad sano excelente con la producción aumentada comparó con cercos sellados (3dB o más), MTX recomienda utilizando un descargar cerco. Todos cercos recomendados se han diseñado y han sido probados completamente por MTX.)
(Pour la qualité solide le mieux possible où l'espace est une prime, MTX recommande utilisant une clôture scellée. Pour la qualité solide excellente avec le production augmenté en comparaison des clôtures scellées (3 dB ou plus), MTX recommande utilisant une clôture donnée vent. Toutes clôtures recommandées ont été conçues et ont été essayées à fond par MTX.)
(Für die bestmögliche gesunde Qualität, wo sperrt eine Prämie ist, empfiehlt MTX daß das Benutzen von einer abgedichteten Einschließung. Für ausgezeichnete gesunde Qualität gibt mit vermehrt